

CENTRAL INTELLIGENCE AGENCY

INFORMATION REPORT

This Document contains information affecting the National Defense of the United States, within the meaning of Title 18, Sections 793 and 794, of the U.S. Code, as amended. Its transmission or revelation of its contents to or receipt by an unauthorized person is prohibited by law. The reproduction of this form is prohibited.

SECRET/CONTROL - U.S. OFFICIALS ONLY

25X1

COUNTRY	Austria	REPORT	
SUBJECT	Production of the SMV Schwechat Oil Refinery	DATE DISTR.	1 March 1954
		NO. OF PAGES	2
DATE OF INFO.		REQUIREMENT NO.	RD
PLACE ACQUIRED		REFERENCES	

25X1

25X1

This is UNEVALUATED Information

THE SOURCE EVALUATIONS IN THIS REPORT ARE DEFINITIVE.
THE APPRAISAL OF CONTENT IS TENTATIVE.
(FOR KEY SEE REVERSE)

25X1

1. Atmospheric Installations.

There are now four atmospheric installations in operation.

No. 1. Amount of crude oil processed (Aderklaa): 21,661.1 tons

Gasoline	16.1%
Kerosene	30.5%
Gas Oil:	18.9%
Residue:	32.9%
Residue (Slop):	00.7%
Loss:	01.1%

The installations was out of operation for 14 days.

No. 2. Amount of crude oil processed (Matzen): 12,695.1 tons

Gasoline:	03.7%
Kerosene:	10.7%
Gas Oil:	23.6%
Residue:	60.9%
Loss:	01.1%

The installation was out of operation for 5 days.

No. 3.a. First Processing. (Primär-Seite).

Amount of crude oil processed (Matzen): 10,945 tons

25 YEAR RE-REVIEW

SECRET/CONTROL - U.S. OFFICIALS ONLY

STATE	X	ARMY	X	NAVY	X	AIR	X	FBI		AEC					
-------	---	------	---	------	---	-----	---	-----	--	-----	--	--	--	--	--

(Note: Washington Distribution Indicated By "X"; Field Distribution By "#".)

SECRET/CONTROL - U.S. OFFICIALS ONLY

- 2 -

Gasoline	05.8%
Kerosene	11.4%
Gas Oil:	22.0%
Residue:	40.4%
Loss:	01.2%

The installation was out of operation for 13 days.

b. Cracking Process (Spalt-Seite-Tiefspaltoven).

Amount of crude oil processed (Matzen):	11,100. tons
Gasoline	29.0%
Cracked Benzin (Spaltgas)	10.0%
Residue:	57.0%
Loss:	04.0%

The installation was out of operation for 13 days.

No. 4. (converted Vacuum Installation).

The installation was put into operation on 20 November 1953. Up to December it was out of operation for 3 days.

Amount of crude oil processed (Matzen, Zistersdorf): 7,277.6 tons

Gasoline:	21.2%
Kerosene:	22.8%
Gas Oil:	24.8%
Residue:	29.5%
"Test Benzin" (samples):	00.7%
Loss:	01.0%

2. Deliveries

The following deliveries were made during November.

<u>Gasoline:</u>	15% Turpentine (Lackbenzin) by rail to Korneuburg refinery. 85% First process benzin (Primärbenzin) to Central Storage Depot, Lobau.
<u>Kerosene:</u>	45% to OROP; 35% to Czechoslovakia; 20% to Central Storage Depot Lobau (pumped).
<u>Gas Oil:</u>	40% to the West; 30% to OROP; 30% to Central Storage Depot, Lobau.
<u>Furnace Oil:</u>	<input type="text"/> 35% to Czechoslovakia; 25 % to Central Storage Depot, Lobau.
<u>Bitumen:</u>	100% to local industry.

25X1

SECRET/CONTROL - U.S. OFFICIALS ONLY